

Tubo per mandata acqua calda

Applicazione: tubo cord per mandata di acqua calda, anche leggermente acida, o liquidi non aggressivi per le industrie chimiche.

Vedi tabella IVG di resistenza chimica.

Temperatura: da -40°C a +120°C.

COSTRUZIONE

Sottostrato: nero, liscio, in gomma EPDM resistente al calore.

Rinforzo: tessuti sintetici ad alta resistenza.

Copertura: nera, liscia (ad impressione tela), in gomma EPDM, resistente al calore, agli agenti atmosferici e all'ozono.

Marcatura: Transfer ad elica di colore verde "IVG....Hot. ".

Hot water discharge hose

Application: Softwall hot water discharge hose, also recommended for use with fluids even slightly acidic in chemical industries.

See IVG chemical resistance tables

Temperature range: -40°C (-40°F) to +120°C (+248°F)

CONSTRUCTION

Tube: black, smooth, heat resistant EPDM rubber compound.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish), EPDM rubber compound, heat, weathering and ozone resistant.

Branding: continuous spiral green brand "IVG..Hot.."





CODICE	diametro interno		diametro esterno		pressione di esercizio		pressione di scoppio (teorica)		peso (nominale)	
CODE	<i>inside diameter</i>		<i>outside diameter</i>		<i>working pressure</i>		<i>burst pressure (theoretical)</i>		<i>weight (nominal)</i>	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft
1192477	10	25/64	20	25/32	10	150	30	450	0.30	0.20
1362399	11	7/16	18	23/32	10	150	30	450	0.20	0.13
1177818	12	15/32	22	7/8	10	150	30	450	0.33	0.23
1282093	13	1/2	20	53/64	10	150	30	450	0.20	0.13
1177494	15	19/32	25	1	10	150	30	450	0.39	0.26
1193201	16	5/8	26	1-1/32	10	150	30	450	0.42	0.28
1186787	18	23/32	28	1-7/64	10	150	30	450	0.45	0.31
1048147	19	3/4	27	1-1/16	10	150	30	450	0.32	0.22
1304569	19	3/4	28	1-7/64	10	150	30	450	0.41	0.28
1177826	20	25/32	30	1-3/16	10	150	30	450	0.50	0.34
1364154	22	7/8	31	1-7/32	10	150	30	450	0.47	0.32
1298313	22	7/8	33	1-19/64	10	150	30	450	0.61	0.41
1177834	25	1	35	1-3/8	10	150	30	450	0.60	0.40
1093851	25	1	37.5	1-1/2	10	150	30	450	0.77	0.52
1177540	30	1-3/16	41.5	1-21/32	10	150	30	450	0.80	0.54
1241320	32	1-1/4	43.5	1-11/16	10	150	30	450	0.85	0.57
1178385	35	1-3/8	48	1-57/64	10	150	30	450	1.07	0.72
1196804	38	1-1/2	50	1-31/32	10	150	30	450	1.04	0.70
1178091	40	1-37/64	54	2-1/8	10	150	30	450	1.29	0.87
1243381	42	1-21/32	54	2-1/8	10	150	30	450	1.15	0.77
1177460	45	1-49/64	61	2-13/32	10	150	30	450	1.63	1.10
1201565	48	1-57/64	58	2-9/32	10	150	30	450	1.00	0.67
1331019	50	1-31/32	68	2-11/16	10	150	30	450	2.09	1.41
1234315	51	2	65.5	2-9/16	10	150	30	450	1.63	1.09
1177770	60	2-3/8	74.5	2-29/32	10	150	30	450	1.88	1.26
1178121	76	3	92	3-5/8	10	150	30	450	2.56	1.72
1178130	90	3-35/64	107	4-7/32	10	150	30	450	3.24	2.17
1180258	102	4	118	4-41/64	10	150	30	450	3.32	2.23

Altri diametri, pressioni e colore di copertura realizzabili su richiesta.

Other sizes, pressure and color of cover available on request.

max lunghezza prodotta <i>max manufactured length</i>		fino al D.I. <i>up to I.D.</i>	
m	ft	mm	inch
120	400	102	4