



PVC hose with rigid PVC spiral, for suction and delivery of liquids, irrigation systems, sewage drains and cesspits. Antistatic versions also available (ON DEMAND Code 911103).



SMOOTH SURFACES

\*\*\*\*\*



FLEXIBILITY

\*\*\*\*\*

SHORE A hardness 57



ABRASION RESISTANCE

\*\*\*



TEMPERATURE RANGE

-25°C +55°C

-13°F +131°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

\*\*\*\*

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23° C	BURSTING PRESSURE 23° C	VACUUM 23° C	Ø RIGID SPIRAL (AXB IF OVAL)	SPIRAL PIT CH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm	mm		m	
1	25	33.8	4.4	500	100	7	21	9	4	7	right	50	IN STOCK
1 1/4	32	40.8	4.4	600	130	6	18	9	4	8.3	right	50	IN STOCK
1 1/2	38	47	4.4	700	150	6	18	9	4	8.5	right	50	IN STOCK
	40	49	4.5	740	160	6	18	9	3.5	8.7	right	50	ON DEMAND
1 3/4	45	55	5	900	180	5.5	16.5	9	5	9.5	right	50	IN STOCK
2	50	61	5.5	1050	200	5	15	9	4.7	11	right	50	IN STOCK
	60	71.2	5.6	1250	240	4.5	13.5	9	5.5	12.1	right	50	IN STOCK
2 1/2	63	75.5	6	1390	250	4.5	13.5	9	5,2x4,8	11	right	50	IN STOCK
	70	82	6	1650	280	4	12	9	5.8	11.5	right	30	IN STOCK
	75	88	6.5	1700	300	4	12	9	6	13	right	30	IN STOCK
3	76	88.8	6.3	1700	300	4	12	9	6	13	right	30	IN STOCK
	80	92.6	6.3	1850	320	3.5	10.5	9	6.2	14	right	30	IN STOCK
3 1/2	89	102.3	6.7	2250	360	3.5	10.5	9	6	15.5	right	30	IN STOCK
3 1/2	90	103.7	6.7	2250	360	3.5	10.5	9	6	14.5	right	30	IN STOCK
	100	114.8	7.4	2700	400	3	9	9	6.5	14.5	right	30	IN STOCK
4	102	116.4	7.4	2700	400	3	9	9	6.5	15	right	30	IN STOCK
	110	125.5	7.5	3100	440	3	9	9	7.4	15.5	right	20	IN STOCK
	120	136	8	3600	480	2.5	7.5	9	7.3	17	right	20	IN STOCK
	125	142.1	8.3	3900	500	2.5	7.5	9	7.8	17.5	right	20	IN STOCK
5	127	143.6	8.3	3900	510	2.5	7.5	9	7.8	17.5	right	20	IN STOCK
	130	147	8.5	4100	520	2.5	7.5	9	8.2	18	right	20	IN STOCK
	133	150	8.5	4200	535	2.5	7.5	9	8.2	18	right	20	IN STOCK
	140	157.4	8.7	4550	560	2	6	9	8.3	18.5	right	20	ON DEMAND
	150	168	9	5000	600	2	6	9	8.5	20	right	20	IN STOCK
6	152	170.4	9	5000	610	2	6	9	8.5	20	right	20	IN STOCK
	160	178.8	9.4	5600	640	2	6	9	8.5	21.5	right	20	IN STOCK
	200	226	13	9500	800	1.5	4.5	9	13	22.5	right	-	IN STOCK
8	203	229.2	13	9500	800	1.5	4.5	9	13	22.5	right	-	IN STOCK
	250	279	14.5	13500	1000	1.5	4.5	9	13x14	23.5	right	-	ON DEMAND
10	254	283	14.5	13500	1000	1.5	4.5	9	14x15	23.5	right	-	IN STOCK
12	304	335.8	15.5	18000	1200	1.5	4.5	9	14x15	24.5	right	-	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.