



PVC hose with rigid PVC spiral, for delivery and suction of food liquids. Light duty version.



SMOOTH SURFACES

\*\*\*\*\*



FLEXIBILITY

\*\*\*\*



ABRASION RESISTANCE

\*\*\*\*



TEMPERATURE RANGE

-5°C +60°C  
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

\*\*



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23° C	BURSTING PRESSURE 23° C	VACUUM 23° C	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		m	
	20	24.8	2.4	210	110	6.5	19.5	7	6.5	right	50	IN STOCK
1	25	29.8	2.4	250	140	6.5	19.5	7	7.4	right	50	IN STOCK
	30	35	2.5	330	175	6	18	7	7.4	right	50	IN STOCK
1 1/4	32	37.2	2.6	350	180	6	18	7	7.7	right	50	IN STOCK
	35	40.4	2.7	400	195	6	18	7	7.7	right	50	IN STOCK
1 1/2	38	43.6	2.8	430	210	6	18	7	7.8	right	50	IN STOCK
	40	46	3	480	220	5.5	16.5	7	7.8	right	50	IN STOCK
1 3/4	45	52	3.5	640	255	5.5	16.5	7	7.8	right	50	IN STOCK
2	50	58.2	4.1	760	275	5.5	16.5	7	8.3	right	50	IN STOCK
2	51	59.5	4.1	760	280	5.5	16.5	7	8.5	right	50	ON DEMAND
	55	63.6	4.3	860	310	5.5	16.5	7	9.8	right	50	ON DEMAND
	60	68.6	4.3	900	330	4	12	7	8.3	right	50	IN STOCK
2 1/2	63	71.2	4.1	970	350	4	12	7	8.5	right	50	IN STOCK
	65	73.2	4.1	1030	360	4	12	7	8.1	right	50	ON DEMAND
	70	79	4.5	1125	450	3	9	7	9	right	50	IN STOCK
	75	84.4	4.7	1200	500	3	9	7	9.5	right	50	IN STOCK
	80	89.4	4.7	1450	550	3	9	7	10.5	right	25	IN STOCK
3 1/2	89	101.8	5.9	1850	630	3	9	7	10.3	right	25	ON DEMAND
	100	112.2	6.1	2200	700	2	2	7	11.3	right	25	ON DEMAND
	110	122	6	2500	770	2	2	7	11.5	right	25	ON DEMAND
	120	133.4	6.7	2800	840	2	2	5	11.5	right	25	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.