



PVC PHF hose with rigid PVC spiral, for heavy-duty use in the wine sector, for suction and delivery of food and alcoholic liquids up to 28%.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE



PHthalate FREE

PHF



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23° C	BURSTING PRESSURE 23° C	VACUUM 23° C	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		m	
1	25	32.6	3.8	400	175	8	24	9	7	right	50	IN STOCK
	30	37.6	3.8	500	210	8	24	9	7.5	right	50	IN STOCK
1 1/4	32	40	4	520	220	8	24	9	7.6	right	50	IN STOCK
	35	43	4	600	240	8	24	9	7.7	right	50	IN STOCK
1 1/2	38	46.4	4.2	700	250	8	24	9	7.8	right	50	IN STOCK
	40	49	4.5	750	260	8	24	9	7.8	right	50	IN STOCK
1 3/4	45	54	4.5	900	290	8	24	9	8	right	50	IN STOCK
2	50	59	4.5	1000	325	8	24	9	8.5	right	50	IN STOCK
	60	71	5.5	1450	380	7	21	9	10	right	50	IN STOCK
2 1/2	63	75	6	1670	400	7	21	9	8.5	right	50	IN STOCK
	70	82	6	1800	450	6	18	9	10.5	right	50	IN STOCK
	75	87	6	1900	490	6	18	9	12	right	50	IN STOCK
	80	93	6.5	2200	530	5	15	9	12	right	50	IN STOCK
3 1/2	90	104	7	2480	600	5	15	9	13.5	right	30	IN STOCK
	100	116	7.5	3300	700	4	12	9	13.5	right	30	IN STOCK
4	102	118	7.5	3300	700	4	12	9	14	right	30	ON DEMAND
	110	126	8	3450	800	4	12	9	14.5	right	30	IN STOCK
	120	136	8	3600	900	4	12	9	17	right	30	IN STOCK
	125	142	8.5	4200	980	4	12	9	12	right	30	IN STOCK
	150	170	10	6300	1350	3	9	9	13.5	right	30	IN STOCK
	200	224	12	8500	1800	2	6	9	22	right	10	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.