



Thermoplastic rubber hose with crush-resistant spiral in PA 6 and textile support in polyester, for suction of car exhaust fumes both on the floor and on overhead reels.



SMOOTH SURFACES

\*\*\*



FLEXIBILITY

\*\*\*



ABRASION RESISTANCE

\*\*



TEMPERATURE RANGE

-40°C +150°C  
-40°F +302°F



CHEMICAL RESISTANCE

TPV table



CRUSHING RESISTANCE

\*\*\*\*\*



CAUTION

The coil is not to be coiled when it is still warm.

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	VACUUM 23°C	TENSILE BREAKING LOAD	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	mm	g/m	mm	bar	m h2o	kg	mm		m	
2	50	68	0.8	-	520	120		5	>130	19	left	30	IN STOCK
	60	80	0.8	-	630	150		3.5	>130	19	left	30	IN STOCK
	75	93	0.8	-	750	180		1.5	>130	19	left	30	IN STOCK
	100	120	0.8	-	1000	230		1	>130	19	left	30	IN STOCK
	125	145	0.8	-	1250	280		0.8	>130	19	left	30	IN STOCK
	150	172	0.8	-	1500	330		0.6	>130	24	left	30	IN STOCK
	200	224	0.8	-	1950	440		0.5	>130	24	left	20	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.