



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement for suction and delivery of oils, blue diesel, diesel and bio diesel.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE

ISO 4649:<90 mm³



TEMPERATURE RANGE

-25°C +60°C
-13°F +140°F



CHEMICAL RESISTANCE

PVC OIL table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 1:4 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	Ø SPIRAL	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	m h2o	mm		mm	m	
3/4	19	28	4.5	450	70	16	12	48	9	8.5	right	1	60	IN STOCK
1	25	35.5	5.2	670	80	16	12	48	9	9	right	1.2	60	IN STOCK
	30	40.6	5.3	770	90	16	12	48	9	9	right	1.2	60	IN STOCK
1 1/4	32	42.5	5.2	800	100	16	12	48	9	9	right	1.2	60	IN STOCK
	35	48	6.5	1050	120	14	10	42	9	9	right	1.4	60	IN STOCK
1 1/2	38	51	6.5	1200	125	14	10	42	9	9	right	1.4	40	IN STOCK
	40	53	6.5	1200	130	14	10	42	9	9	right	1.4	40	IN STOCK
1 3/4	45	58	6.5	1340	140	12	10	36	9	9	right	1.4	40	IN STOCK
	2	50	64	1730	150	12	10	36	9	9	right	1.6	40	IN STOCK
2 1/2	60	74	7	1950	180	12	10	36	9	9	right	1.6	40	IN STOCK
	63	77	7	2030	190	12	10	36	9	9	right	1.6	40	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.