



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement with copper wire for an anti-static rendering, with outer cover made of anti-abrasive PU, for suction and delivery of oils, blue diesel, diesel and bio diesel.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE

ISO 4649: <30 mm³

TEMPERATURE RANGE

-25°C +60°C

-13°F +140°F



CHEMICAL RESISTANCE

PVC OIL table



CRUSHING RESISTANCE



ANTISTATIC

Wire resistance 0,075 Ohm/m

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 1:4 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	Ø SPIRAL	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	m h2o	mm		mm	m	
3	76	90.5	7.25	2700	210	10	8	30	9	13.5	right	2	30	IN STOCK
	80	94.5	7.25	2800	220	10	8	30	9	14	right	2	30	IN STOCK
3 1/2	90	106	8	3250	250	10	8	30	9	14	right	2	30	IN STOCK
4	102	117.5	7.75	3700	300	10	8	30	9	14.5	right	2	30	IN STOCK
	120	137	8.5	4750	450	8	6	24	9	15	right	2.5	20	IN STOCK
5	127	144	8.5	5300	480	7	5	21	9	15	right	2.5	20	IN STOCK
	150	167.5	8.75	6300	550	5	3	15	9	15.5	right	2.5	20	IN STOCK
6	152	169.5	8.75	6350	550	5	3	15	9	15.5	right	2.5	20	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.