

SPLENDOR LT



The Splendor LT is a versatile three-position earmuff. It offers powerful protection against noise for a wide range of applications. Due to its fully plastic construction, the Splendor LT is dielectric and the 3-Position-Headband enables it to be worn with other head protection and safety equipment.

- Light and durable structure
- Slim and ergonomic design
- Head strap allows the use behind the head- and under the chin position
- Headband rotation of 360 degrees
- Weight; 217 g
- Color yellow
- SNR 30 dB / NRR 24 dB / SLC80 30dB

SNR 30 dB

NRR 24 dB

MADE IN FINLAND

ATTENUATION VALUES	H = 33 dB		M = 28 dB		L = 20 dB		SNR = 30 dB		
Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean attenuation (dB)	15.5	19.8	31.4	35.6	34.9	36.5	36.4	39.3	41.8
Std. Deviation	2.1	2.7	2.5	2.9	3.4	2.7	3.1	3.1	3.8
APV-value (84%)	13.4	17.1	28.9	32.7	31.5	33.8	33.3	36.2	38.0

ADDITIONAL INFORMATION

SNR	30
NRR	24
Attenuation	High
Helmet Mounted	No
Level Dependent	No
Bluetooth	No
Communication	No
High Visibility	No
Dielectric	Yes