



Transparent PVC hose with shock-resistant rigid PVC spiral, for fish farming and carrying fish products and heavy duty applications.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-25°C +55°C
-13°F +131°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	Ø RIGID SPIRAL (AXB IF OVAL)	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm	mm		m	
4	102	121.6	10	2900	200	2.5	7.5	10	7.8	14	right	5	ON DEMAND
5	127	149	11	3600	300	2.5	7.5	9.5	8.8	17.5	right	5	ON DEMAND
6	152	175.4	11.5	5600	350	2	6	9.5	12x10	20.5	right	5	ON DEMAND
8	203	230.2	13.5	9200	600	2	6	9.5	13,5x11,5	22	right	5	ON DEMAND
10	254	290	18	14500	1000	1.5	4.5	9.5	18x16	30	right	5	ON DEMAND
12	305	344.8	20	19000	1500	1.5	4.5	9.5	18,5x16,5	29	right	5	ON DEMAND
14	355	396	20	22000	2200	1.25	3.75	9	18 x 17,5	30	right	5	ON DEMAND
16	407	450	21.5	28000	3000	1	3	9	20,5 x 19	33.5	right	5	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.