

915065 SUPER RAGNO N 80 BAR



PVC hose with double polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, liquids under pressure.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
5/16	8	15	3.5	170	20	80	64	48	240	100	IN STOCK
3/8	10	19	4.5	240	30	80	64	48	240	100	IN STOCK
1/2	13	23	5	340	40	80	64	48	240	100	IN STOCK
5/8	16	26	5	450	55	80	64	48	240	100	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.