

# 915150 RAGNO AIR 20 BAR



Soft PVC hose with polyester yarn reinforcement and intermediate bonding PU adhesive layer for passage of air under pressure. (\*) Double polyester yarn reinforcement.



SMOOTH SURFACES

\*\*\*\*\*



FLEXIBILITY

\*\*\*\*



ABRASION RESISTANCE

\*\*\*



TEMPERATURE RANGE

-5°C +60°C  
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

\*\*\*



OZONE RESISTANCE

\*\*\*\*\*

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
3/16	5	10.5	2.75	92	20	20	18	16	60	100	IN STOCK
1/4	6	14	4	175	25	20	18	16	60	100	IN STOCK
	7	16	4.5	220	20	20	18	16	60	100	IN STOCK
5/16	8	15	3.5	175	28	20	18	16	60	100	ON DEMAND
5/16	8	17	4.5	245	30	20	18	16	60	100	IN STOCK
3/8	10	19	4.5	270	32	20	18	16	60	100	IN STOCK
1/2	13	23	5	380	40	20	18	16	60	100	IN STOCK
5/8	16	26	5	440	50	20	18	16	60	50	IN STOCK
3	19	30	5.5	560	60	20	18	16	60	60	IN STOCK
1	25	37	6	765	85	20	18	16	60	60	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.