



Flexible layflat NITRILIC RUBBER (NBR) hose with polyester yarn reinforcement, resistant to elongation, for pressurised delivery of air.



SMOOTH SURFACES



FLEXIBILITY

*



ABRASION RESISTANCE



TEMPERATURE RANGE

-20°C +80°C
-4°F +176°F



CHEMICAL RESISTANCE

NBR



CRUSHING RESISTANCE

*

Ø I.D.	Ø I.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	TENSILE STRENGTH	COIL LENGTH	AVAILABILITY
inch	mm	mm	g/m	mm	bar	bar	kg	m	
3/4	20	2.3	230	400	30	90	1180	60	ON DEMAND
1	25	2.3	265	450	30	90	1350	60	ON DEMAND
1 1/4	32	2.3	310	500	30	90	1750	60	ON DEMAND
1 1/2	38	2.3	365	750	20	60	2000	60	ON DEMAND
1 3/4	45	2.3	395	850	20	60	2400	60	ON DEMAND
2	52	2.3	510	1300	20	60	2900	60	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.